Power Distribution Units (PDUs)

PlusMetered 1 Series



- > Measurement +/-1% accuracy to measure six parameters of
 - AC power
- > High temperature environment operation
- Durable Metal Housing
- Cord Retention Tray
- Overload Protection
- Surge Suppression

Specifications:

MODEL	PlusMetered 1-15A
INPUT	
Nominal Voltage	110Vac-240Vac
Frequency	50Hz-60Hz
Max, Current	15A
Type of Connection	NEMA 5-15P *1
Length of Cable	3M
OUTPUT	
Over Current Protection	15A
Q'ty of Socket	8
Type of Socket	NEMA 5-15R
DISPLAY	
LCD	AC voltage, AC current, active power, power factor, frequency and total power consumption
MEASUREMENT	
Voltage	AC 40.0-300.0V(110Vac-240Vac Universal)
Current	0.00-100.0A(110Vac-240Vac Universal)
Active Power	0-30000W / 0-45000W
Frequency	45.0Hz-65.0Hz
Total Power Consumption	0-99999Kwh
Power Facotor	0.00-1.00PF
SURGE PROTECTION	
Max. Total Surge Absorption Current	24,000Amp.
Max. Total Surge Absorption Energy	1200Joules
PHYSICAL	
Rack Height	1U
Cord Retention Tray	Optional
Dimension(L*W*H)	480*62*45mm
Weight	1.5kgs
ENVIORNMENT	
Operating Temperature	0-50°C
Operating Humidity	0-95%

^{*}Product specifications are subject to change without further notice.

