PlusMetered 3 Series



- Measurement +/-1% accuracy to measure six parameters of AC power
- Features hot-swappable MOV surge protection
- Equipped with 3 independent control switches
- High temperature environment operation
- Durable Metal Housing
- Cord Retention Tray
- Overload Protection
- Surge Suppression

Specifications:

MODEL	PlusMetered 3-30A
INPUT	
Nominal Voltage	110Vac-240Vac
Frequency	50Hz-60Hz
Max, Current	30A
Type of Connection	NEMA 5-30P *1
Length of Cable	3M
OUTPUT	
Over Current Protection	30A
Q'ty of Socket	24
Type of Socket	NEMA 5-15R
DISPLAY	
LCD	AC voltage, AC current, active power, power factor, frequency and total power consumption
MEASUREMENT	
Voltage	AC 40.0-300.0V(110Vac-240Vac Universal)
Current	0.00-100.0A(110Vac-240Vac Universal)
Active Power	0-30000W / 0-45000W
Frequency	45.0Hz-65.0Hz
Total Power Consumption	0-99999Kwh
Power Facotor	0.00-1.00PF
SURGE PROTECTION	
Max. Total Surge Absorption Current	20,000Amp.
Max. Total Surge Absorption Energy	4000Joules
PHYSICAL	
Rack Height	1U
Cord Retention Tray	Optional
Independent Control Switch	3pcs
Dimension(L*W*H)	1320*65*45mm
Weight	3.4kgs
Installation Format	Vertical
ENVIORNMENT	
Operating Temperature	0-50°C
Operating Humidity	0-95%

*Product specifications are subject to change without further notice.

APlus® UPS SYSTEMS